



## 50G SFP56 to 50G SFP56 DAC



**0.5~3m**

**PVC Black**

### Key Features

- Support 53.125G PAM4
- InfiniBand HDR & Ethernet compatible
- Maximum link length up to 3m
- Single Wire Size: 26AWG~30AWG
- Maximum power consumption: <0.05W each end
- Case temperature range: 0°C to 70°C
- 3.3V Power Supply
- Hot Pluggable
- RoHS Compliance

### Applications

- Data center & Networking Equipment
- Servers/Storage Devices
- High Performance Computing (HPC)
- Switches/Routers

### Supported Standards

- SFP MSA
- SFF-8472
- IEEE 802.3cd



### Ordering Information

LEPP-KK1xxxC		50G SFP56 to 50G SFP56 DAC – 0.5~3m			
Ordering P/Ns	Description	Length	AWG	Cable	NOTE
LEPP-KK1010C	50G SFP56 to 50G SFP56 DAC	1.0m	30 AWG	PVC Black	
LEPP-KK1020C	50G SFP56 to 50G SFP56 DAC	2.0m	28 AWG	PVC Black	
LEPP-KK1030C	50G SFP56 to 50G SFP56 DAC	3.0m	26 AWG	PVC Black	
xxx define DAC cable length					

## Disclaimer

Images are for illustrative purposes only and may not accurately represent the actual product. Specifications and appearances are subject to change without prior notice.

The information provided in this datasheet is subject to change without notice. Lumulus Technologies assumes no responsibility for any errors or omissions. Performance may vary depending on application and operating conditions. Product specifications are provided for reference only and do not constitute a warranty.

For assistance and more information, please contact your sales representative or write to [sales@lumulus.com](mailto:sales@lumulus.com)

### Lumulus Technologies, Inc. USA

#### Headquarter

9685 Via Excelencia Suite 106  
San Diego, CA 92126  
USA

 (+1) 858-397-2228

 [www.lumulus.com](http://www.lumulus.com)

 [sales@lumulus.com](mailto:sales@lumulus.com)



### Lumulus Technologies, Inc. (Thailand Branch)

#### Production Site

30/30 Moo2, Tambol Wangchula  
Amphur, Wagnoi, Phranakorn  
Sri Ayutthaya - 13170, Thailand



- **Lumulus Tech offers 24/7 support,**
- with experts ready to assist with all your technical needs and questions.



[tech.support@lumulus.com](mailto:tech.support@lumulus.com)



[sales@lumulus.com](mailto:sales@lumulus.com)