

## 25G SFP28 to 25G SFP28 ACC



6~9m

PVC Black

### Key Features

- Support 25.78125G NRZ
- InfiniBand EDR & Ethernet compatible
- Maximum link length up to 9m
- Single Wire Size: 26AWG~28AWG
- Maximum power consumption:<0.3W each end
- Case temperature range: 0°C to 70°C
- 3.3V Power Supply
- Hot Pluggable
- RoHS Compliance

### Applications

- Data center & Networking Equipment
- Servers/Storage Devices
- High Performance Computing (HPC)
- Switches/Routers

### Supported Standards

- SFP MSA
- SFF-8472
- IEEE 802.3by



### Ordering Information

LFPP-UU1xxxC		25G SFP28 to 25G SFP28 ACC – 6~9m			
Ordering P/Ns	Description	Length	AWG	Cable	NOTE
LFPP-UU1060C	25G SFP28 to 25G SFP28 ACC	6.0m	28 AWG	PVC Black	
LFPP-UU1075C	25G SFP28 to 25G SFP28 ACC	7.5m	26 AWG	PVC Black	
LFPP-UU1090C	25G SFP28 to 25G SFP28 ACC	9.0m	26 AWG	PVC Black	
xxx define ACC cable length					

## Disclaimer

Images are for illustrative purposes only and may not accurately represent the actual product. Specifications and appearances are subject to change without prior notice.


The information provided in this datasheet is subject to change without notice. Lumulus Technologies assumes no responsibility for any errors or omissions. Performance may vary depending on application and operating conditions. Product specifications are provided for reference only and do not constitute a warranty.

For assistance and more information, please contact your sales representative or write to [sales@lumulus.com](mailto:sales@lumulus.com)

## Lumulus Technologies, Inc. USA

### Headquarter

9685 Via Excelencia Suite 106  
San Diego, CA 92126  
USA

 (+1) 858-397-2228

 [www.lumulus.com](http://www.lumulus.com)

 [sales@lumulus.com](mailto:sales@lumulus.com)



## Lumulus Technologies, Inc. (Thailand Branch)

### Production Site

30/30 Moo2, Tambol Wangchula  
Amphur, Wagnoi, Phranakorn  
Sri Ayutthaya - 13170, Thailand



**Lumulus Tech offers 24/7 support,**  
with experts ready to assist with all your technical needs and questions.



[tech.support@lumulus.com](mailto:tech.support@lumulus.com)



[sales@lumulus.com](mailto:sales@lumulus.com)